

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

PROTECH BALCONY

1.2 Relevant identified uses of the substance or mixture and uses advised against

Preparation for building and construction: transparent, non-film, breathable liquid for waterproofing balconies, Terraces and tiled staircases, pedestrian, without demolishing the existing pavement.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

AZICHEM Srl

Street : Via G. Gentile 16/A

Postal code/city : 46044 Goito (MN)

Telephone : +390376604185/604365

Telefax : +39 0376 604398

Information contact : info@azichem.com

1.4 Emergency telephone number

Centro Antiveleni di Milano +39 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) (24h)
Centro Antiveleni di Pavia +39 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)
Centro Antiveleni di Bergamo +39 800 883300 (CAV Ospedali Riuniti - Bergamo)
Centro Antiveleni di Firenze +39 055 7947819 (CAV Ospedale Careggi - Firenze)
Centro Antiveleni di Roma +39 06 3054343 (CAV Policlinico Gemelli - Roma)
Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)
Centro Antiveleni di Napoli +39 081 7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Flam. Liq. 2 ; H225 - Flammable liquids : Category 2 ; Highly flammable liquid and vapour.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; CAS No. : 64742-48-9

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY ; CAS No. : 64742-82-1

Hazard statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H315 Causes skin irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P314 Get medical advice/attention if you feel unwell.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
P403+P235 Store in a well-ventilated place. Keep cool.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; REACH registration No. : 01-2119463258-33 ; EC No. : 265-150-3; CAS No. : 64742-48-9

Weight fraction : $\geq 75 - < 80$ %
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

TRIETHOXYISOBUTYLSILANE ; EC No. : 402-810-3; CAS No. : 17980-47-1

Weight fraction : $\geq 10 - < 15$ %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315

ETHYL ACETATE ; REACH registration No. : 01-2119475103-46 ; EC No. : 205-500-4; CAS No. : 141-78-6

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY ; EC No. : 265-185-4; CAS No. : 64742-82-1

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304 STOT RE 1 ; H372

Additional information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove victim out of the danger area. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

In case of skin contact

Wash immediately with: Water Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician. In case of skin reactions, consult a physician.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

4.2 Most important symptoms and effects, both acute and delayed

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

May be fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure.
Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder alcohol resistant foam Carbon dioxide (CO2) Water mist

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for firefighters

Remove persons to safety.

Special protective equipment for firefighters

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Clear spills immediately. Wear a self-contained breathing apparatus and chemical protective clothing.

For non-emergency personnel

Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up

The contaminated area should be cleaned up immediately with: Water Retain contaminated washing water and dispose it.

6.4 Reference to other sections

Reference to other sections Safe handling: see section 7 Personal protection equipment: see section 8

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Protective measures

Specific requirements or handling rules

Do not breathe dust. Do not breathe gas/fumes/vapour/spray. See section 8.

Advices on general occupational hygiene

Normal precautions taken when handling chemicals should be observed.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

7.2 Conditions for safe storage, including any incompatibilities

Only use containers specifically approved for the substance/product.

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect against UV-radiation/sunlight Humidity.

Hints on joint storage

Storage class : 3

Storage class (TRGS 510) : 3

Keep away from

Store at least 3 metres apart from: Chemicals/products that react together readily

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 400 ppm / 1500 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 06.11.2015

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL Consumer (local) (ETHYL ACETATE ; CAS No. : 141-78-6)

Exposure route : Inhalation

Exposure frequency : Long-term (repeated)

Limit value : 367 mg/m³

Limit value type : DNEL Consumer (local) (ETHYL ACETATE ; CAS No. : 141-78-6)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 734 mg/m³

Limit value type : DNEL Consumer (systemic) (ETHYL ACETATE ; CAS No. : 141-78-6)

Exposure route : Oral

Exposure frequency : Long-term (repeated)

Limit value : 4,5 mg/kg

Limit value type : DNEL Consumer (systemic) (ETHYL ACETATE ; CAS No. : 141-78-6)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 734 mg/m³

Limit value type : DNEL Consumer (systemic) (ETHYL ACETATE ; CAS No. : 141-78-6)

Exposure route : Dermal

Exposure frequency : Long-term (repeated)

Limit value : 37 mg/kg

Limit value type : DNEL Consumer (systemic) (ETHYL ACETATE ; CAS No. : 141-78-6)

Exposure route : Inhalation

Exposure frequency : Long-term (repeated)

Limit value : 367 mg/m³

Limit value type : DNEL worker (local) (ETHYL ACETATE ; CAS No. : 141-78-6)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 1468 mg/m³
Limit value type : DNEL worker (local) (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 734 mg/m³
Limit value type : DNEL worker (systemic) (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 1468 mg/m³
Limit value type : DNEL worker (systemic) (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 63 mg/kg
Limit value type : DNEL worker (systemic) (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 734 mg/m³

PNEC

Limit value type : PNEC aquatic, freshwater (ETHYL ACETATE ; CAS No. : 141-78-6)
Limit value : 0,26 mg/l
Limit value type : PNEC aquatic, intermittent release (ETHYL ACETATE ; CAS No. : 141-78-6)
Limit value : 1,65 mg/l
Limit value type : PNEC aquatic, marine water (ETHYL ACETATE ; CAS No. : 141-78-6)
Limit value : 0,02 mg/l
Limit value type : PNEC sediment, freshwater (ETHYL ACETATE ; CAS No. : 141-78-6)
Limit value : 1,25 mg/kg
Limit value type : PNEC sediment, marine water (ETHYL ACETATE ; CAS No. : 141-78-6)
Limit value : 0,12 mg/kg
Limit value type : PNEC Soil (ETHYL ACETATE ; CAS No. : 141-78-6)
Limit value : 0,24 mg/kg
Limit value type : PNEC Secondary Poisoning (ETHYL ACETATE ; CAS No. : 141-78-6)
Limit value : 0,2 g/kg
Limit value type : PNEC sewage treatment plant (STP) (ETHYL ACETATE ; CAS No. : 141-78-6)
Limit value : 650 mg/l

8.2 Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment



When using do not eat, drink, smoke, sniff.

Eye/face protection

Suitable eye protection

Eye glasses with side protection

Skin protection

Hand protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

Tested protective gloves must be worn

Respiratory protection

Quarter-face mask (DIN EN 140) Half-face mask (DIN EN 140) Filtering Half-face mask (DIN EN 149)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Safety relevant basis data

Aspect			clear liquid
Colour			colourless
Odour			No data available
Melting point/melting range :	(1013 hPa)		No data available
Vapour density	((air = 1))	>	1
Initial boiling point and boiling range :	(1013 hPa)		115 °C
Decomposition temperature :			No data available
Self flammability			No data available
Flash point :			21 - 35 °C
Flammability (solid, gas)			Data not available
Lower explosion limit :			No data available
Upper explosion limit :			No data available
Explosive properties			Data not available
Vapour pressure	(20 °C)		No data available
Density :	(20 °C)		0,79 - 0,81 g/cm ³
Water solubility :	(20 °C)		insoluble
pH :			not applicable
Log Pow	(20 °C)		not applicable
Viscosity :	(20 °C)		10 - 30 mPa.s
Odour threshold			Data not available
Evaporation rate			0,12
Maximum VOC content (EC) :			84,8 Wt %
Oxidizing properties			Not oxidising

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

See section 7. No additional measures necessary.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter : LD50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; CAS No. : 64742-48-9)
Exposure route : Oral
Species : Rat
Effective dose : > 5000 mg/kg
Parameter : LD50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Oral
Species : Rat
Effective dose : 4934 mg/kg
Method : OECD 401

Acute dermal toxicity

Parameter : LD50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; CAS No. : 64742-48-9)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 5000 mg/kg
Parameter : LD50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 20000 mg/kg

Acute inhalation toxicity

Parameter : LC50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; CAS No. : 64742-48-9)
Exposure route : Inhalation
Species : Rat
Effective dose : > 4951 mg/m³
Exposure time : 4 h
Parameter : LC50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Inhalation
Species : Rat
Effective dose : > 22,5 mg/l
Exposure time : 6 h

Irritant and corrosive effects

Causes skin irritation.

Sensitisation

not sensitising.

Repeated dose toxicity (subacute, subchronic, chronic)

Subacute oral toxicity

Parameter : NOAEL(C) (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Oral
Species : Rat
Effective dose : 900 mg/kg bw/day

Subacute inhalation toxicity

Parameter : NOAEL(C) (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Inhalation
Species : Rat
Effective dose : 350 ppm

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Reproductive toxicity

Developmental toxicity/teratogenicity

One generation reproduction toxicity test

Parameter : NOAEL(C) (ETHYL ACETATE ; CAS No. : 141-78-6)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

Species : Mouse
Effective dose : 13800 mg/kg bw/day

Two generation reproduction toxicity test

Parameter : NOAEL(C) (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Mouse
Effective dose : 20700 mg/kg bw/day

SECTION 12: Ecological information

Do not allow uncontrolled discharge of product into the environment.

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; CAS No. : 64742-48-9)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 10 - 30 mg/l
Exposure time : 96 h
Parameter : LC50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Salmo trutta fario (L) (Freshwater trout)
Effective dose : 230 mg/l
Exposure time : 96 h

Acute (short-term) daphnia toxicity

Parameter : EC50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; CAS No. : 64742-48-9)
Species : Daphnia
Effective dose : 22 - 46 mg/l
Exposure time : 48 h
Parameter : EC50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Daphnia magna (Big water flea)
Effective dose : 165 mg/l
Exposure time : 48 h

Chronic (long-term) daphnia toxicity

Parameter : NOEC (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Daphnia pulex (water flea)
Effective dose : 2,4 mg/l
Exposure time : 21 g

Acute (short-term) algae toxicity

Parameter : EC50 (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; CAS No. : 64742-48-9)
Species : Algae
Effective dose : > 1000 mg/l
Exposure time : 72 h

Chronic (long-term) algae toxicity

Parameter : NOEC (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Scenedesmus subspicatus
Effective dose : > 100 mg/l
Exposure time : 72 h

Bacteria toxicity

Parameter : EC50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Photobacterium phosphoreum
Effective dose : 5870 mg/l
Exposure time : 15 min

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (ETHYL ACETATE ; CAS No. : 141-78-6)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

Effective dose : > 70 %
Exposure time : 28 g

12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) (ETHYL ACETATE ; CAS No. : 141-78-6)
Concentration : 30

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Dispose according to legislation.

SECTION 14: Transport information

14.1 UN number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY · ETHYL ACETATE)

Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY · ETHYL ACETATE)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), HYDROTREATED HEAVY · ETHYL ACETATE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 33
Tunnel restriction code : D/E
Special provisions : 640D · LQ 11 · E 2
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special provisions : LQ 11 · E 2
Hazard label(s) : 3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 2
Hazard label(s) : 3

14.4 Packing group

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

II

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) 1907/2006/CE (REACH). Regulation (EC) No 1272/2008 (CLP). Regulation (EU) 2015/830 requirements for the compilation of safety data sheets. Commission Regulation (EC) No 790/2009/CE (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 286/2011 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 618/2012 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 487/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 758/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 944/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 605/2014 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 1297/2015 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008).

Other regulations (EU)

Regulation (CE) 1907/2006: Substance of very high concern included in the SVHC Candidate List

None

National regulations

Italy: Legislative Decree 81/2008 (Consolidated Law on protection of health and safety at work), as amended and Directive 2009/161/UE - chemical risk assessment in accordance with Title IX

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Sea transport (IMDG)

16.2 Abbreviations and acronyms

LEGENDA:

ADR: Accord européen relative au transport international des marchandises dangereuses par route (accordo europeo relativo al trasporto internazionale delle merci pericolose su strada)
ASTM: ASTM International, originariamente nota come American Society for Testing and Materials (ASTM)
EINECS: European Inventory of Existing Commercial Chemical Substances (Registro Europeo delle Sostanze)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

	chimiche in Commercio)
EC(0/50/100):	Effective Concentration 0/50/100 (Concentrazione Effettiva Massima per 0/50100% degli Individui)
LC(0/50/100):	Lethal Concentration 0/50/100 (Concentrazione Letale per 0/50100% degli Individui)
IC50:	Inhibitor Concentration 50 (Concentrazione Inibente per il 50% degli Individui)
NOEL:	No Observed Effect Level (Dose massima senza effetti)
NOEC:	No Observed Effect Concentration (Concentrazione massima senza effetti)
LOEC:	Lowest Observed Effect Concentration (Concentrazione massima alla quale è possibile evidenziare un effetto)
DNEL:	Derived No Effect Level (Dose derivata di non effetto)
DMEL:	Derived Minimum Effect Level (Dose derivata di minimo effetto)
CLP:	Classification, Labelling and Packaging (Classificazione, Etichettatura e Imballaggio)
CSR:	Rapporto sulla Sicurezza Chimica (Chemical Safety Report)
LD(0/50/100):	Lethal Dose 0/50/100 (Dose Letale per 0/50/100% degli Individui)
IATA:	International Air Transport Association (Associazione Internazionale del Trasporto Aereo)
ICAO:	International Civil Aviation Organization (Organizzazione Internazionale dell'Aviazione Civile)
Codice IMDG:	International Maritime Dangerous Goods code (Codice sul Regolamento del Trasporto Marittimo)
PBT:	Persistent, bioaccumulative and toxic (sostanze persistenti bioaccumulabili e tossiche)
RID:	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regolamento concernente il trasporto Internazionale ferroviario delle merci Pericolose)
STEL:	Short term exposure limit (limite di esposizione a breve termine)
TLV:	Threshold limit value (soglia di valore limite)
TWA:	Time Weighted Average (media ponderata nel tempo)
UE:	Unione Europea
vPvB:	Very persistent very bioaccumulative (sostanze molto persistenti e molto bioaccumulabili)
N.D.:	Non disponibile.
N.A.:	Non applicabile
VwVwS.:	Text of Administrative Regulation on the Classification of Substances hazardous to waters into Water Hazard Classes (Verwaltungsvorschrift wassergefährdende Stoffe – VwVwS)
PNEC:	Predicted No Effect Concentration
PNOS:	Particulates not Otherwise Specified
BOD:	Biochemical Oxygen Demand
COD:	Chemical Oxygen Demand
BCF:	BioConcentration Factor
TRGS :	Technische Regeln für Gefahrstoffe -Technical Rules for Hazardous Substances, defined by The Federal Institute for Occupational Safety and Health, Germany
LCLo:	Lethal Concentration Low (La minima concentrazione letale)
ThOD:	Theoretical Oxygen Demand

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

calculated.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

16.6 Training advice

None

16.7 Additional information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROTECH BALCONY
Revision date : 04.06.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
